

HOBO® MX1102 Logger

Bluetooth Smart-enabled CO₂, temperature and relative humidity data logger

Onset's HOBOMX1102 CO₂ logger makes it more convenient than ever to measure and record CO₂ in buildings and other non-condensing environments. It measures CO₂ from 0 – 5,000 parts per million (ppm) – and our free HOBOMobile app allows you to access data right from your mobile phone or tablet within a 100-foot range.

The MX1102 also features a USB port so it can be used with a computer running HOBOWare Pro graphing and analysis software.

Supported Measurements:

CO₂, Temperature, Relative Humidity, Dew Point

Key Advantages:

- Wireless communication via Bluetooth Low Energy (BLE)
- Six-month battery life at 5-minute CO₂ logging rate
- Easy to deploy and offload using free HOBOMobile App
- Visual and audible high & low alarm thresholds
- Self-calibrating CO₂ sensor technology ensures optimal accuracy at lower maintenance costs



Minimum System Requirements:



HOBOMobile



Mobile device



*iOS 8.3, 8.4 & 9.0, or Android 4.4, 5.0, 5.1 and Bluetooth 4.0 or later



► For complete information and accessories, please visit: www.onsetcomp.com

Part number	MX1102
Memory	84,650 Measurements
Logging Rate	1 second to 18 hours
Battery Life	6 months, typical with logging and sampling intervals of 5 minutes or slower; 6 months or less with logging and sampling intervals faster than 5 minutes while logging CO ₂ , user replaceable, 4AA
Dimensions	7.62 x 12.95 x 4.78 cm (3.0 x 5.1 x 1.88 inches)
CO₂	
Range	0 to 5,000 ppm
Accuracy	±50 ppm ±5% of reading at 25°C (77°F), less than 70% RH and 1,013 mbar
Warm-up Time	15 seconds
Calibration	Auto or manual to 400 ppm
Non-linearity	<1% of FS
Temperature	
Range	0° to 50°C (32° to 122°F)
Accuracy	±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F)
Resolution	0.024°C at 25°C (0.04°F at 77°F)
Response Time	12 minutes to 90% in airflow of 1 m/s (2.2 mph)
Relative Humidity	
Range	1% - 90%RH, non-condensing
Accuracy	±2.0% from 20%RH to 80%RH typical to a maximum of ±4.5% including hysteresis at 25°C (77°F); below 20%RH and above 80%RH ±6% typical
Hysteresis	±2%RH
Resolution	0.01%RH
Drift	<1%RH per year typical
Response Time	CO₂: 1 minute to 90% in airflow of 1 m/s (2.2 mph), Temp: 12 minutes to 90% in airflow of 1 m/s (2.2 mph), RH: 1 minute to 90% in airflow of 1 m/s (2.2 mph)
CE compliant	Yes

Note: Temp & RH NIST certification services available for this product. Please visit onsetcomp.com, or call us at 1-800-564-4377.

Contact Us

